



SE7 TECHNICAL DATA SHEET



ETERNO ADJUSTABLE PAVING SUPPORT WITH SELF LEVELING HEAD

SE 7



ITEM SPECIFICATION

"MRP Supports Eterno" type pedestal for raised floors with adjustable height from 7.25" - 10.75" 185mm to 275mm, provided of bi-component self levelling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8" 205 mm for resting on the laying surface, one extension element, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of 5/32" 4mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head. **Accessories Available** - Locking Piece for Fixed Head Applications and Locking PINS for IPE Wood Deck Tiles.

PRODUCT RANGE

Adjustable Pedestal Support

PRODUCT NAME

SE 7

CHARACTERISTICS

Adjustable in highness. Bicomponent material (PP and rubber) self leveling head.

Regulation key for highness adjustment

Easy removable tabs

Security lock system to prevent unlocking.

RAW MATERIAL

Polypropylene and rubber (head top finishing)

ENVIRONMENTAL IMPACT

recyclable material - non dangerous



APPLICATIONS SURFACES

On any waterproofing membrane, or any insulating panel or any compact and solid surface

APPLICATIONS AREA

Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	UNIT	VALUE	TOLERANCE
BASE DIAMETER	8"	205mm	+/- mm 1,0
BASE THICKNESS	1/4"	5mm	+/- mm 0,2
HEAD DIAMETER	6"	155mm	+/- mm 0,8
LAYING SURFACE OF THE BASE	49.6 sq"	330cm ²	+/- cmq 5
MINIMUM HEIGHNESS	7.25"	185mm	+/- mm 1,0
MAXIMUM HEIGHNESS	10.75"	275mm	+/- mm 1,5
TABS THICKNESS	5/32"	4mm	+/- mm 0,2
TABS HIGHNESS	1/2"	18mm	+/- mm 0,2
WEIGHT	1.66 lbs	0,754kg	+/- 5 %

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* <small>(calculated at medium highness, between minimum and maximum extension)</small>		KN	16,14
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* <small>(calculated at medium highness, between minimum and maximum extension)</small>		KN	12,28
SLOPE CORRECTION		%	0 - 5
SHORE		Shore d	70 (+/- 3)

*Tests made by Civil and Environmental Department of University of Padova. 1 KN = 98,6 Kg

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

*Tests made by Giordano S.p.A. Institute of Bellaria-Iaeca Marina (RN)-Italy

PACKAGING AND STORAGE	
PIECES PER BOX	25 SE4 + 25 P1 Extensions = SE7
PIECES PER PALLET	tbd
BOX DIMENSION	28 x 21 x 20+16 x 16 x 16
BOX WEIGHT	35 lbs + 15 lbs
PALLET DIMENSION	tbd

The packing of the supports is made of boxes. The final pallets are wrapped with a polyethylene film. We recommend to store indoor, pallets to be protected from the rain.

LAYING OF THE PRODUCT	
	The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by MRP Supports (Eterno) at any time without notice.

Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of MRP Supports (Eterno). All rights reserved.



MRP Supports
 3310 N Benzing Road
 Orchard Park, NY 14127
 Ph: 800-828-8424
 Web: www.mrpsupports.com
 Email: mrp@mrpsupports.com