



## STAR T & STAR B TECHINCAL DATA SHEET



### ADJUSTABLE SUPPORT STAR.T & STAR B



ITEM SPECIFICATION	
	Supply and installation of "STAR.T" raised floor supports. The supports are made of two polypropylene elements with diameter of 6" (152mm) and with a height of 9/16" (15 mm), in the upper part there are 4 spacer that are 1/2" (12 mm) tall and thick 5/32" (4 mm). There are holes in the base for water drainage. There are housings for various accessories and a hole for the adjustment key.
PRODUCT RANGE	PEDESTAL
PRODUCT NAME	<b>STAR.T</b>
CHARACTERISTICS	Minimum height 1/3" (8mm) using only the upper part; Height of complete pedestal using also base: 3/8" (10mm); Adjustable in height up to 9/16" (15mm); Possibility to use Star B extensions elements with a height of 3/16" (5mm); Maximum height reached with extensions: 1-1/8" (30mm); Holes for water drainage; Hole for adjustment key insertion; 4 spacer tabs height 1/2" (12mm) thickness 5/32" (4mm) pre-cutted and removable; Slot for inserting accessories for joists:
PAW MATERIAL	Polypropylene
ENVIROMENTAL IMPACT	Recyclable material – non dangerous
APPLICATION SURFACE	On any waterproofing membrane surface, or any insulating panel or any compact and solid surface.
APPLICATION AREA	With any self-supporting prefabricated element for outdoor flooring, with a minimum thickness of 9/6" (15 mm)

CHARACTERISTICS	Unit Inches	Unit mm	TOLLERANCE
BASE DIAMETER	6"	152	+/- mm 1,0
BASE THICKNESS	1/3"	8	+/- mm 0,2
MINIMUM HEIGHT	1/3"	8	+/- mm 1,0
TABS THICKNESS	5/32"	4	+/- mm 0,2
TABS HEIGHT	1/2"	12	+/- mm 0,2

WEIGHT	.21 lbs	0.097kg	+/- 5 %
<b>TECHNICAL PROPERTIES</b>			
CENTRAL COMPRESSION LIMIT RESISTANCE* (calculated at average height, between minimum and maximum)		kN	35.53
SHORE		Shore d	70 (+/- 3)
* Tests carried out by the Department of Civil, Building and Environmental Engineering of the University of Padua. 1 KN = 217 lbs (98.6 Kg)			
<b>PACKAGING AND STORAGE</b>			
PIECES PER BOX		250	
PIECES PER PALLET		tbd	
BOX DIMENSION		tbd	
BOX WEIGHT		tbd	
PALLET DIMENSION		tbd	
<b>LAYING OF PRODUCT</b>			
	The product is simply laid on the laying area, with no need of any glue or fixing		

The above data are relevant to current production and may be changed or updated by MRP Supports (Eterno) at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of MRP Supports (Eterno). All rights reserved.



MRP SUPPORTS, LLC  
 3310 N BENZING ROAD  
 ORCHARD PARK, NY 14127  
 PH: 800-828-8424  
 Web: [www.mrpsupports.com](http://www.mrpsupports.com)  
 Email: [mrp@mrpsupports.com](mailto:mrp@mrpsupports.com)